

HFTA/HFTG FRONT TERMINAL BATTERIES



The SEC UK series of HFTA and HFTG VRLA batteries have a compact footprint, excellent power density and a front terminal construction, specifically designed to fit 19" & 23" ETSI racks and cabinets. The battery design features; extra heavy duty plates, high tin, robust busbars and ABS casing, which makes it a high reliability product, suitable for all high integrity standby applications.

HFTA Front Terminal AGM Batteries

Features:

- Front terminal for ease of installation and maintenance
- Low self-discharge for long shelf life
- Absorbed Glass Matt (AGM) technology assures no free electrolyte
- High gas recombination efficiency
- Extended design life >12 years
- High tin calcium alloy
- High cyclic
- Deep discharge

Type	Alternative Reference	Volts	Ah C20	Ah C10	Ah C5	Dimensions (mm)			Approx. Weight (Kg)	Layout	Terminal
						Length	Width	Total Height			
HFTA55-12	12FTA 55	12	58.4	55	48.4	277	105	222	16.3	3	M6
HFTA80-12	---	12	84.3	80	76.3	564	114	187	26	3	M6
HFTA80-12T	12FTA 80	12	84.8	80	70	395	110	285	27.5	3	M8
HFTA100-12	12FTA 100	12	106	100	88	395	110	285	31	3	M8
HFTA105-12	12FTA 105	12	110.2	105	92	507	109	238	31	3	M8
HFTA125-12	12FTA 125	12	132.6	125	110	550	110	285	39.8	3	M8
HFTA155-12	12FTA 155	12	162.8	155	135	550	110	285	44.5	3	M8
HFTA180-12	12FTA 180	12	180	170	148	550	126	280	54	3	M8

HFTG Front Terminal GEL Batteries

Features:

- Front terminal for ease of installation and maintenance
- Low self-discharge for long shelf life
- High tin calcium alloy
- Deep discharge
- GEL technology assures no free electrolyte
- High gas recombination efficiency
- Extended design life >12 years
- High tin calcium alloy

Type	Alternative Reference	Volts	Ah C20	Ah C10	Ah C5	Dimensions (mm)			Approx. Weight (Kg)	Layout	Terminal
						Length	Width	Total Height			
HFTG55-12	12FTG 55	12	58	55	47	277	106	222	17.5	3	M6
HFTG80-12	12FTG 80	12	70	65.8	57.8	564	114	187	26.7	3	M6
HFTG100-12	12FTG 100	12	96	90	79.2	394	110	285	35	3	M6
HFTG150-12	12FTG 150	12	144	135	118.8	551	110	288	47.4	3	M6
HFTG180-12	12FTG 175	12	158	150	132	550	126	280	52	3	M6

